THESE ENGINEERING DRAWINGS HAVE BEEN PREPARED BY SOUTHERN HYDRAULIC CYLINDER, INC. ("SHC") BASED ON PARTICULAR INFORMATION AND DESIGN SPECIFICATIONS PROVIDED BY THE CUSTOMER. SHC ASSUMES NO RESPONSIBILITY FOR SUCH PARTICULAR INFORMATION OR DESIGN SPECIFICATIONS PROVIDED AND ASSUMES NO THIS PRINT CONTAINS CONFIDENTIAL INFORMATION AND IS THE PROPERTY OF SOUTHERN HYDRAULIC CYLINDER, INC. AND RESPONSIBILITY FOR AN SPECIFICA PRINCIPLAR INFORMATION ON DESIGN SPECIFICATIONS PROVIDED AND ASSUMES NO RESPONSIBILITY FOR ANY SPECIFIC APPLICATION OF THE PRODUCT RESULTING FROM THE DESIGN SPECIFICATIONS. CUSTOMER SHALL INDEMNIFY SHE CAGINST ANY CLAIM BY ANY PARTY FOR DAMAGES BASED ON ANY ERROR. OMMISSION OR FALLT IN THE PARTICULAR INFORMATION OR DESIGN SPECIFICATIONS PROVIDED BY THE CUSTOMER. IS NOT TO BE COPIED OR REPRODUCED WITHOUT THE EXPRESSED CONSENT OF SOUTHERN HYDRAULIC CYLINDER, INC. 30.00 (REF) 1/2"-14 NPT PORT 8.81 - 4.00 2.00 Ø 1.266 Ø 2.00 4.63 +1/8 -.00 Ø 1.875 2.00 Ø 3.00 Ø 4.00 - 8.50 ± .14 RETRACTED --- 1.13 ---42.50 ± .16 STROKE 51.00 ± .30 EXTENDED NOTES: 1. SEAL KIT NUMBER: 32SA. 2. PAINT NUMBER: UN1263 RED OXIDE PRIMER 3. MAX. OPERATING PRESSURE: 2500 PSI 4. CYLINDER WT. (LBS): APPROX. 60 5. OIL CAPACITY (GAL.): .61 RETRACTED; 1.54 EXTENDED MACHINING TOLERENCES
UNLESS OTHERWISE SPECIFIED
ONE PLACE X = ±.1
TWO PLACES .XXX = ±.03
THREE PLACES .XXX = ±.0010
FOUR PLACES .XXXX = ±.0010
ALL ANGLES = ±2° CHECKED PPROVED BREAK ALL SHARP EDGES .010 X 45° SCALE DO NOT SCALE DRAWING FOR MACHINING DIMENSIONS CHANGE DATE TELESCOPIC CYLINDER ASSEMBLY

CUSTOMER STD. SHC CYLINDER

FILE SE

3243TR